

# Generation of sub-100-fs pulses at up to 200 MHz repetition rate from a passively mode-locked Yb-doped fiber laser

F. Ö. Ilday, J. Chen, and F. X. Kärtner

*Department of Electrical Engineering and Computer Science and Research Laboratory of Electronics,*

*Massachusetts Institute of Technology, Cambridge, Massachusetts 02139-4307*

[ilday@mit.edu](mailto:ilday@mit.edu)

**Abstract:** Generation of sub-100-fs pulses at repetition rates of 100-200 MHz from a passively mode-locked Yb-fiber laser via nonlinear polarization rotation is reported. The limitations to the repetition rate in terms of the pulse dynamics and the physical size of the cavity are discussed. We determine that physical size of the components dictate the maximum repetition rate and discuss the implications of a shorter cavity on the pulse shaping as a consequence of a weaker dispersion map.

© 2005 Optical Society of America

**OCIS codes:** (320.7090) Ultrafast lasers; (140.3510) Lasers, fiber

---

## References and links

1. F. O. Ilday, J. R. Buckley, W. G. Clark, F. W. Wise, "Self-similar evolution of parabolic pulses in a laser," *Phys. Rev. Lett.* **92**, 3902-3905 (2004).
2. F. O. Ilday, J. R. Buckley, H. Lim, F. W. Wise, and W. G. Clark, "Generation of 50-fs, 5-nJ pulses at 1.03  $\mu\text{m}$  from a wave-breaking-free fiber laser," *Opt. Lett.* **28**, 1365-1367 (2003).
3. J. R. Buckley, F. W. Wise, F. O. Ilday, and T. Sosnowski, "Femtosecond fiber lasers with pulse energies above 10 nJ," to be published in *Optics Letters*.
4. F. O. Ilday, J. Buckley, L. Kuznetsova, and F. W. Wise, "Generation of 36-femtosecond pulses from a ytterbium fiber laser," *Opt. Express* **11**, 3550-3554 (2003), <http://www.opticsexpress.org/abstract.cfm?URI=OPEX-11-26-3550>.
5. H. Lim, F. O. Ilday, and F. W. Wise, "Generation of 2-nJ pulses from a femtosecond Yb fiber laser," *Opt. Lett.* **28**, 660-662 (2003).
6. J. R. Buckley, F. O. Ilday, H. Lim, and F. W. Wise, "Self-similar pulses as a route to low repetition-rate femtosecond fiber lasers," *Proceedings of the Conference on Lasers and Electro-Optics (Optical Society of America, San Francisco, CA, 2004)*, paper CthK7.
7. J. Rauschenberger, T. M. Fortier, D. J. Jones, J. Ye, and S. T. Cundiff, "Control of the frequency comb of a mode-locked Erbium doped-fiber laser," *Opt. Lett.* **24**, 1404-1410 (2002).
8. F. Tauser, A. Leitenstorfer, and W. Zinth, "Amplified femtosecond pulses from an Er: fiber system: Nonlinear pulse shortening and self-referencing detection of the carrier-envelope phase evolution," *Opt. Express* **11**, 594-600 (2003), <http://www.opticsexpress.org/abstract.cfm?URI=OPEX-11-6-594>.
9. B. R. Washburn, S. A. Diddams, and N. R. Newbury, J. W. Nicholson, M. F. Yan, and C. G. Jorgensen, "Phase-locked, erbium-fiber-laser-based frequency comb in the near infrared," *Opt. Lett.* **29**, 250-252 (2004).
10. T. R. Schibli, K. Minoshima, F.-L. Hong, H. Inaba, A. Onae, H. Matsumoto, I. Hartl, and M. E. Fermann, "Frequency metrology with a turnkey all-fiber system," *Opt. Lett.* **29**, 2467-2469 (2004).
11. J. Limpert, T. Clausnitzer, A. Liem, T. Schreiber, H.-J. Fuchs, H. Zellmer, E.-B. Kley, and A. Tuennermann, "High-average-power femtosecond fiber chirped-pulse amplification system," *Opt. Lett.* **28**, 1984-1986 (2003).
12. D. J. Jones, S. Namiki, D. Barbier, E. P. Ippen, and H. A. Haus, "116-fs soliton source based on an Er-Yb codoped waveguide amplifier," *IEEE Phot. Technol. Lett.* **10**, 666-668 (1998).
13. B. C. Collings, K. Bergman, S. T. Cundiff, S. Tsuda, J. N. Kutz, J. E. Cunningham, W. Y. Jan, M. Koch, and W. H. Knox, "Short cavity Erbium/Ytterbium Fiber Lasers Mode-locked with a saturable Bragg reflector," *IEEE J. Sel. Top. Quantum Electron.* **3**, 1065 (1997).

14. M. Hofer, M. E. Fermann, F. Harberl, M. H. Ober, and A. J. Schmidt, "Mode-locking with cross-phase and self-phase modulation," *Opt. Lett.* **16**, 502-504 (1991).
15. N. J. Doran, and D. Wood, "Nonlinear-optical loop mirror," *Opt. Lett.* **13**, 56-58 (1998).
16. F. O. Ilday, F. W. Wise, and T. Sosnowski, "High-energy femtosecond stretched-pulse fiber laser with a nonlinear optical loop mirror," *Opt. Lett.* **27**, 1531-1533 (2002), and references therein.
17. Y. Deng, M. W. Koch, F. Lu, G. W. Wicks, and W. H. Knox, "Colliding-pulse passive harmonic mode-locking in a femtosecond Yb-doped fiber laser with a semiconductor saturable absorber," *Opt. Express* **12**, 3872-3877 (2004), <http://www.opticsexpress.org/abstract.cfm?URI=OPEX-12-16-3872>.
18. K. Tamura, J. Jacobson, H. A. Haus, E. P. Ippen, and J.G. Fujimoto, "77-fs pulse generation from a stretched-pulse mode-locked all-fiber ring laser," *Opt. Lett.* **18**, 1080-1082 (1993).
19. F. O. Ilday, F. W. Wise, and F. X. Kaertner, "Possibility of self-similar pulse evolution in a Ti:sapphire laser," *Opt. Express* **12**, 2731-2738 (2004), <http://www.opticsexpress.org/abstract.cfm?URI=OPEX-12-12-2731>.
20. A. Berntson, N. J. Doran, W. Forysiak, and J. H. B. Nijhof, "Power dependence of dispersion-managed solitons for anomalous, zero, and normal path-average dispersion," *Opt. Lett.* **23**, 900-902 (1998).

There is much recent interest in fiber lasers as sources of femtosecond pulses due to their excellent stability, compact size, and low cost. Rapid progress has been made with Yb-fiber lasers operating at 1  $\mu\text{m}$  in the past two years. A new mode-locking regime exploiting self-similar pulse propagation has been demonstrated [1] and these lasers now routinely generate sub-100 fs pulses with over 5 nJ of energy at repetition rates of 30-50 MHz [2, 3]. These lasers were operated at relatively low repetition rates, typically at  $\sim 30$  MHz [2, 3, 5]. To our knowledge, only the lower limit to the repetition rate arising from residual birefringence has been studied [6]. Thus, it seems natural to explore the upper limitations to the repetition rate.

In addition, there is practical motivation; many applications demand repetition rates higher than  $\sim 100$  MHz. A leading example is optical frequency metrology, where several groups are exploring the use of fiber lasers [7, 8, 9, 10]. In this case, a high repetition rate ( $\gtrsim 150$  MHz) is desirable to attain sufficiently large comb line spacing. Higher repetition rates can be achieved with harmonically mode-locked lasers as well. However, active harmonic mode-locking leads to picosecond pulses and passive harmonic mode-locking is not stable enough for these applications. Furthermore, in combination with a Yb fiber amplifier [11], powerful, femtosecond pulses can be obtained, which would be particularly suited for applications such as micro-machining. To date, the repetition rates of fundamentally mode-locked fiber lasers with pulse durations of 100 fs or less have barely reached 100 MHz at 1  $\mu\text{m}$  [5], and 130 MHz (with an Er/Yb-codoped glass waveguide amplifier) at 1.55  $\mu\text{m}$  [12]. Repetition rates up to 300 MHz have been reported from Er-fiber lasers, however the pulse duration were limited to nearly 500 fs [13]. Here, we report systematically scaling the fundamental repetition rate of an Yb fiber laser up to 200 MHz, while preserving sub-100-fs pulse duration. We choose Yb fiber as the gain medium since it offers the highest gain per length among readily available fibers. Increasing the repetition rate of fiber lasers encounters two distinct challenges: (i) in practice, the cavity length is ultimately limited by the physical size of the components constituting the laser cavity, (ii) more fundamentally, there is a threshold power for initiating passive mode-locking.

The commonly used techniques for passive mode-locking of fiber lasers rely on intensity-dependent phase shifts accumulated by the pulse as it traverses through the fiber. Nonlinear polarization evolution (NPE) [14] is the most commonly used due to its large modulation depth ( $\sim 50\%$ ) and essentially instantaneous response. If a polarizing beamsplitter is used, the rejected light is extracted out of the cavity and acts as a useful output port. Other techniques include the nonlinear optical loop mirror [15] and its variants, which also have been demonstrated to generate high-energy, short pulses [16]. However, these techniques require longer fiber lengths, rendering them unsuitable for high repetition rate operation. Decreasing the cavity roundtrip time causes less energy to be stored in the cavity, limiting the peak power of the pulse, and for given power, a shorter fiber section results in smaller nonlinear phase shift to be accumulated.



ious pulse evolutions previously observed in fiber lasers: soliton-like pulses at negative GVD, dispersion-managed solitons around zero GVD [18] and some indications of self-similar pulses at positive GVD [1].




Fig. 2. Evolution of the pulse spectrum as the cavity dispersion is changed from  $-10500 \text{ fs}^2$  to  $+7400 \text{ fs}^2$ .

The effect of increasing the repetition rate has consequences reaching beyond that of a higher mode-locking power threshold: the shorter fiber segment corresponds to a smaller swing in the dispersion map created by the positive GVD fibers and the negative GVD from the gratings. At sufficiently short lengths, the pulse would cease to stretch and compress and would simply experience the average GVD. At a repetition rate of 162 MHz, this effect is not severe yet and the typical transformation of the spectral shape reported in Ref. [5] is observed experimentally as the dispersion is adjusted from  $-10500 \text{ fs}^2$  to  $+7400 \text{ fs}^2$  (Fig. 2). Due to uncertainties in the GVD coefficients and the fiber lengths, we estimate that the absolute values of net GVD have an error of  $\pm 1500 \text{ fs}^2$ . However, relative changes to the net GVD are known precisely since the GVD of the gratings is well known. The pulse duration after external dechirping ranges from 70 fs to 135 fs. The corresponding characteristic dispersive length in the fiber segment ranges from 6.4 cm to 23.0 cm, which suggests an intracavity breathing ratio of  $\sim 4$ , given the fiber length of 90 cm. This value is in contrast to the high-energy fiber lasers that were operated at 30-40 MHz repetition rate, commonly attaining intracavity breathing ratios of 10-30 [1, 2].

We describe the performance of the laser at 162 MHz with a view toward applications. In accordance with previous results [4], we attain the shortest pulses at small net negative GVD. At a net GVD of  $-1300 \text{ fs}^2$ , the pulses rejected at the NPE port are dechirped to yield an intensity autocorrelation width of 96 fs, from which we infer a pulse width of 70 fs, assuming a Gaussian pulse shape (Fig. 3). The output pulse energy is 150 pJ, limited by the pump power. Measuring the power of a portion of the intracavity beam, which is reflected off the first grating, enables us to accurately determine the pulse energy in the fiber segment to be 0.65 nJ. Although multiple pulsing is not a serious concern at this energy level, long-range autocorrelation measurements and the rf spectra were checked to rule out this possibility. The rf spectrum shows that the pulse contrast is at least 60 dB (at the measurement bandwidth of 10 Hz) (Fig. 3).

Even though mode-locked operation is possible at large positive GVD (Fig. 2), there are differences from previous results reported for similar Yb fiber lasers at lower repetition rates




Fig. 3. (a) Optical spectrum at cavity dispersion of  $-1300 \text{ fs}^2$  at 162 MHz repetition rate. (b) Intensity autocorrelation of the pulses after external dechirping. Inset: rf spectrum of the pulses.

due to the weaker dispersion map. It was not possible to operate this laser exhibiting self-similar pulse (similariton) evolution with all of its characteristic features [1]. Operation at  $+6000 \text{ fs}^2$  and  $+7400 \text{ fs}^2$  has little intra-cavity breathing and the spectral shape is different from that of similariton lasers. For the latter case, the amount of dispersion necessary to dechirp the pulses is twice that provided by the grating pair inside the cavity. From the measured autocorrelation and the known magnitudes of dispersion from the gratings, we determine that the pulse always maintains a large positive chirp within cavity, varying from  $\sim 3.5$  times the transform-limit at the beginning of the fiber section to  $\sim 7$  times at the end of the fiber section. Even though these pulses exhibit the monotonic stretching of positively chirped pulses in the fiber segment as in self-similar propagation, the pulse breathing is much weaker and the pulse shape does not appear to be parabolic. This deviation is not surprising, considering that the self-similar mode of operation necessitates significant reshaping of the pulse during each roundtrip [19]. We expect that it would be possible to attain true self-similar operation at higher repetition rates with the use of specialty fibers with a higher dispersion coefficient to ensure sufficient pulse breathing and a tighter mode confinement (alternatively, higher pump power) for stronger nonlinear effects.




Fig. 4. (a) Optical spectrum at cavity dispersion of  $-8400 \text{ fs}^2$  at 200 MHz repetition rate. (b) Intensity autocorrelation of the pulses after external dechirping. Inset: rf spectrum of the pulses.

It was possible to increase the repetition rate up to 200 MHz by reducing the total fiber length to 66 cm, which is finally limited by the physical size of the cavity elements. At this repetition rate, mode-locking could be obtained only when the net GVD of the cavity is anomalous. Attempts at mode-locking for GVD smaller than  $-3000 \text{ fs}^2$  have failed. Mode-locking at large

negative GVD is not more difficult than at 162 MHz, so we attribute failure of mode-locking at zero and positive GVD partially to insufficient strength of the dispersion map [20], or simply to the self-starting mechanism being too weak. At net GVD of  $-8400 \text{ fs}^2$ , where mode-locking is obtained easily, the pulse energy is 145 pJ (average power of 29 mW). The optical spectrum, autocorrelation, and rf spectrum are shown in Fig. 4. The inferred pulse duration is 85 fs (assuming a Gaussian pulse shape). The mode-locked train and the rf spectrum indicate clean mode-locking. Since the physical size of the cavity restricts us to  $\sim 200$  MHz, we conclude that insufficient nonlinearity is not the immediate limitation to repetition rate in femtosecond fiber lasers mode-locked by NPE. We estimate that the repetition rate can be increased to 250-300 MHz by shrinking the free-space region and minimizing the undoped fiber length with a careful engineering effort.

In conclusion, we have demonstrated sub-100 fs pulse generation from a fiber laser with repetition rates up to 200 MHz. This laser is a reliable and inexpensive tool constructed entirely from commercially available components. Along with previous results for low repetition rates [6], it is now established that passively mode-locked Yb fiber lasers producing  $\sim 100$ -fs pulses can be operated with repetition rates anywhere between 20 and 200 MHz. With external amplification, this laser can serve as an ideal seed source for super-continuum generation for applications that benefit from higher repetition rates, such as frequency metrology, micromachining, and bio-medical imaging.

### **Acknowledgments**

This work was supported by the Office of Naval Research under grant ONR-N00014-02-1-0717, and the Air Force Office of Scientific Research under grant FA9550-04-1-0011. FÖI acknowledges support by the Research Laboratory of Electronics through a research fellowship. The authors thank F. W. Wise, J. R. Buckley, O. D. Mücke, and F. J. Grawert for discussions.